

## Surface Mount Type

# POSCAP

Series : TC




### Features

- Guaranteed at 125 °C
- RoHS compliance, Halogen free

### Specifications


Size code	D2E	D3L	D4
Category temperature range	-55 °C to +125 °C		
Rated voltage range	4 V.DC to 6.3 V.DC	2.5 V.DC to 10 V.DC	
Category voltage range	3.2 V.DC to 5.0 V.DC	2.0 V.DC to 8.0 V.DC	
Rated capacitance range	100 µF to 330 µF	150 µF to 680 µF	330 µF to 1000 µF
Capacitance tolerance	±20 % (120 Hz / + 20 °C)		
Leakage current	Please see the attached characteristics list		
Dissipation factor (tan δ)	Please see the attached characteristics list		
Surge voltage (V.DC)	Rated voltage × 1.15		
Endurance	+125 °C, 1000 h Category temperature range voltage applied		
	Capacitance change	Within ±20 % of the initial value	
	tan δ	≤ 2 times of the initial limit	
	DC leakage current	≤ 2 times of the initial limit	
Damp heat (Steady State)	+60 °C, 90 % to 95 %, 500 h, No-applied voltage		
	Capacitance change	Within +50 %, -20 % of the initial value (ETCF1000M6H (5H))	
	tan δ	≤ 1.5 times of the initial limit	
	DC leakage current	≤ 3 times of the initial limit	

### Marking



R. Voltage (VDC)	2.5	4.0	6.3	10.0
Code	e	g	j	A

### Dimensions (not to scale)



Unit : mm

Size code	L±0.3	W±0.2	H±0.2*1	S±0.2	W1±0.1
D2E	7.3	4.3	1.8	1.3	2.4
D3L	7.3	4.3	2.8	1.3	2.4
D4	7.3	4.3	3.8	1.3	2.4

\* Externals of figure are the reference.  
\* 1 ±0.1 : D2E

## Characteristics list

Series	Rated voltage (V.DC)	Rated temp. (°C)	Category voltage (V.DC)	Category temp. (°C)	Rated capacitance (μF)	Case size (mm)			Size code	Specifications				Standard		
						L	W	H		Ripple* <sup>1</sup> current (mAr.m.s.)	ESR* <sup>2</sup> (mΩ max.)	tan δ* <sup>3</sup>	LC* <sup>4</sup> (μA)	Part number	Min. Packaging Qty (pcs)	
TCE	2.5	105	2.0	125	680	7.3	4.3	2.8	D3L	3500	12	0.10	170.0	ETCE680MCL	2500	
		105	2.0	125		7.3	4.3	2.8		3100	15	0.10	170.0	ETCE680MFL	2500	
		105	2.0	125	1000	7.3	4.3	3.8	D4	3900	15	0.15	250.0	ETCE1000MF	2000	
	4	105	3.2	125	150	7.3	4.3	1.8	D2E	2800	18	0.10	60.0	4TCE150MI	3000	
		105	3.2	125		7.3	4.3	1.8		3100	15	0.10	88.0	4TCE220MF	3000	
		105	3.2	125	220	7.3	4.3	1.8		2800	18	0.10	88.0	4TCE220MI	3000	
		105	3.2	125		7.3	4.3	1.8		2400	25	0.10	88.0	4TCE220M	3000	
		105	3.2	125	330	7.3	4.3	1.8	2800	18	0.10	132.0	4TCE330MI	3000		
		105	3.2	125		7.3	4.3	1.8	2400	25	0.10	132.0	4TCE330M	3000		
		105	3.2	125	470	7.3	4.3	2.8	D3L	3500	12	0.10	188.0	4TCE470MCL	2500	
		105	3.2	125		7.3	4.3	2.8		3100	15	0.10	188.0	4TCE470MFL	2500	
		105	3.2	125		7.3	4.3	2.8		2800	18	0.10	188.0	4TCE470MIL	2500	
		6.3	105	5.0	125	100	7.3	4.3	1.8	D2E	2800	18	0.10	63.0	6TCE100MI	3000
	105		5.0	125	7.3		4.3	1.8	2400		25	0.10	63.0	6TCE100M	3000	
	105		5.0	125	150	7.3	4.3	1.8	3100		15	0.10	94.5	6TCE150MF	3000	
	105		5.0	125		7.3	4.3	1.8	2800		18	0.10	94.5	6TCE150MI	3000	
	105		5.0	125	220	7.3	4.3	1.8	2400		25	0.15	94.5	6TCE150M	3000	
	105		5.0	125		7.3	4.3	1.8	2800		18	0.15	138.6	6TCE220MI	3000	
	105		5.0	125	330	7.3	4.3	2.8	D3L	2400	25	0.15	138.6	6TCE220M	3000	
	105		5.0	125		7.3	4.3	2.8		3100	15	0.10	207.9	6TCE330MFL	2500	
10	105		5.0	125	470	7.3	4.3	3.8	D4	2800	18	0.10	207.9	6TCE330MIL	2500	
	105		5.0	125		7.3	4.3	3.8		2400	25	0.10	207.9	6TCE330ML	2500	
	105		5.0	125	680	7.3	4.3	3.8	D4	3500	18	0.15	296.1	6TCE470MI	2000	
	105		5.0	125		7.3	4.3	3.8		3000	25	0.15	296.1	6TCE470M	2000	
	105	5.0	125	680	7.3	4.3	3.8	D4	3500	18	0.15	428.4	6TCE680MI	2000		
	105	5.0	125		7.3	4.3	3.8		3000	25	0.15	428.4	6TCE680M	2000		
TCF	2.5	105	8.0	125	220	7.3	4.3	2.8	D3L	2800	18	0.10	220.0	10TCE220MIL	2500	
		105	8.0	125		7.3	4.3	2.8		2400	25	0.10	220.0	10TCE220ML	2500	
	4	105	8.0	125	330	7.3	4.3	3.8	D4	3000	25	0.10	330.0	10TCE330M	2000	
		2.5	105	2.0	125	680	7.3	4.3	2.8	D3L	4400	6	0.10	170.0	ETCF680M6L	2500
			105	2.0	125		7.3	4.3	2.8		4400	7	0.10	170.0	ETCF680M7L	2500
			105	2.0	125	1000	7.3	4.3	2.8	D4	4400	10	0.10	170.0	ETCF680ML	2500
			105	2.0	125		7.3	4.3	3.8		6100	5	0.10	170.0	ETCF680M5H	2000
		105	2.0	125	1000	7.3	4.3	3.8	D4	6100	5	0.10	250.0	ETCF1000M5H	2000	
	105	2.0	125	7.3		4.3	3.8	5600		6	0.10	250.0	ETCF1000M6H	2000		
	6.3	105	3.2	125	330	7.3	4.3	2.8	D3L	4000	12	0.10	132.0	4TCF330ML	2500	
		105	3.2	125	470	7.3	4.3	2.8		4400	10	0.10	188.0	4TCF470ML	2500	
		105	3.2	125	680	7.3	4.3	3.8	D4	4400	10	0.10	272.0	4TCF680MAH	2000	
		105	5.0	125	220	7.3	4.3	2.8	D3L	6100	5	0.10	138.6	6TCF220M5L	2500	
		105	5.0	125		7.3	4.3	2.8		4600	9	0.10	138.6	6TCF220M9L	2500	
105	5.0	125	330	7.3	4.3	2.8	D3L	4000	12	0.10	138.6	6TCF220ML	2500			
105	5.0	125		7.3	4.3	2.8		3900	9	0.10	207.9	6TCF330M9L	2500			
10	105	10.0	125	150	7.3	4.3	3.8	D4	4400	10	0.10	296.1	6TCF470MAH	2000		
10	105	10.0	125	150	7.3	4.3	2.8	D3L	3600	15	0.10	150.0	10TCF150ML	2500		

\*1 Ripple current (100 kHz/ +45 °C), \*2 ESR (100 kHz/+20 °C) \*3 tan δ (120 Hz/+20 °C) \*4 After 5 minutes

◆ Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".