



CSS0528P Series SMD WIRE WOUND POWER INDUCTORS (SHIELDED)





Rev. A

A. Electrical Specifications:

P/N	Marking	Inductance (μH)	Test Freq. (KHz)	DCR Max. (m Ω)	Rated Current (A)
CSS0528P-2R5N	2R5	2.5	10	18	2.60
CSS0528P-3R0N	3R0	3.0	10	24	2.40
CSS0528P-4R2N	4R2	4.2	10	31	2.20
CSS0528P-5R3N	5R3	5.3	10	38	1.90
CSS0528P-6R2N	6R2	6.2	10	45	1.80
CSS0528P-8R2N	8R2	8.2	10	53	1.60
CSS0528P-100N	100	10	10	65	1.30
CSS0528P-120N	120	12	10	76	1.20
CSS0528P-150N	150	15	10	103	1.10
CSS0528P-180N	180	18	10	110	1.00
CSS0528P-220N	220	22	10	122	0.90
CSS0528P-270N	270	27	10	175	0.85
CSS0528P-330N	330	33	10	189	0.75
CSS0528P-390N	390	39	10	212	0.70
CSS0528P-470N	470	47	10	250	0.62
CSS0528P-560N	560	56	10	305	0.58
CSS0528P-680N	680	68	10	355	0.52
CSS0528P-820N	820	82	10	463	0.46
CSS0528P-101N	101	100	10	520	0.42

B. Dimensions: mm (Inch)

Series	a	b	c	d	e	f	g	h	i	k
CSS0528P	5.7 (0.224)	5.7 (0.224)	3.0 (0.118)	8.2 (0.323)	5.5 (0.217)	5.5 (0.217)	2.0 (0.079)	2.15 (0.085)	2.0 (0.079)	6.3 (0.248)
Tol.	± 0.3 (0.012)	± 0.3 (0.012)	Max.	Max.	Typ.	Typ.	Typ.	Typ.	Typ.	Typ.



C. General Information:

1. CSS0528P-xxx_, "CSS0528P" = P/N, "xxx" = Inductance, "_" = Tolerance.
2. Tolerance "_": N: $\pm 30\%$, M: $\pm 20\%$, L: $\pm 15\%$
3. Operating temperature range: -30°C to $+100^{\circ}\text{C}$ (Including self-generated heat).
4. Storage temperature: -40°C to $+85^{\circ}\text{C}$.
5. Inductance measured using the HP4284A and Chroma 1320 & 3302.
6. DCR measured using Chroma 16502 milliohm meter.
7. Inductance drop no more than 35% of initial value at rated current, temperature rise $\Delta t < 40^{\circ}\text{C}$
8. Inductance and Current range: From 2.5 μH (2.60A) to 100.0 μH (0.42A).
9. MSL: Level 1.

D. Applications:

1. Game Consoles
2. Set Top Boxes
3. Cables Modems
4. Computers
5. Mobile Communication Devices (Cell Phones, Radios, etc.)
6. PDA, LCD, DVD, BRP, HD.




CSS0528P Series SMD WIRE WOUND POWER INDUCTORS (SHIELDED)

Rev. A

E. Characteristics Curve:

Inductance vs. Frequency



Inductance vs. DC Current

