


SCOCXOH family package DIL 14

HC-MOS output 10 to 120 MHz



DIMENSIONS



Pin out

- Pin 1 = Voltage control
- Pin 7 = GND
- Pin 8 = Fout
- Pin 14 = Vdd

All dimensions in mm typical

Oven control quartz crystal oscillator
Fundamental mode frequency
High shock and vibration resistance
Wide temperature range
Low aging
Customer specification on request
Very fast warm up
Low power consumption
Swiss made quality

DESCRIPTION:

This DIL 14 package has been specially designed for the applications:

- Digital switching
- Telecom transmission
- Sonet / SDH / DWDM / FDM/36 / WIMAX
- Airbone equipments
- Battery operated systems
- Instrumentation
- Radio Transceiver

The OCXO are supplied on trays (50 pcs/tray).

ELECTRICAL CHARACTERISTICS 25°C

Frequency versus temperature		ΔF/F		see table 1 (without air flow)	
A: 0 to +60°C					
B: -20 to +70°C					
C: -40 to +85°C					
Frequency long term aging 1)		ΔF/F		ppm	
long term aging 10 years		≤ 40MHz		>40MHz	
long term aging 1 st year		< ± 2.5		< ± 4	
		≤ ± 0.3		≤ ± 1	
Frequency control range see table 3		Vc		ppm	
		≤ 40MHz		>40MHz	
		≥ ± 2.5		≥ ± 4	
Supply voltage		Vdd		3.3 / 5	
Input current		Idd		see table 2	
Output signal sine wave				HC-MOS compatible	
Symmetry at Vdd/2				40 / 60	
				%	
Rise & fall time (without load)				≤7	
				nS	
Level "0" & "1"				<0.4V> Vcc-0.5	
				V	
Load min / max				3/47	
				pF	
Start-up time		t		<5	
				ms	
Frequency stability versus load ± 10%		ΔF/F		≤ ± 30	
				ppb	
Warm-up within ± 0.1 ppm at 25°C		Vdd		3.3	
		t		5	
				≤ 120	
				≤ 60	
				s	
Stability versus Vdd		ΔF/F		< ± 0.1	
				ppm	
Short term stability 0.1 to 30s		Tau		< 1	
5E-11 typ at 1s				E-10	
Phase noise typical				10MHz	
Static conditions				100MHz	
BW = 1Hz					
10Hz				-105	
100Hz				-135	
1 kHz				-150	
10 kHz				-160	
100kHz				-160	
				-90	
				-120	
				-140	
				-150	
				-155	
				dBc/ Hz	

1) <± 1 E-9 / day after 30 days operating

TABLE 1: Vdd = 3.3V

Operating Temperature range	Vdd = 3.3V ± 0.15V	
	Version standard	Version high stability
A = 0 to +60°C	≤ ± 75 ppb	≤ ± 50 ppb
B = -20 to +70°C	≤ ± 150 ppb	≤ ± 75 ppb
C = -40 to +85°C	≤ ± 250 ppb	≤ ± 100 ppb

TABLE 1: Vdd = 5V

Operating Temperature range	Vdd = 5V ± 0.2V	
	Version standard	Version high stability
A = 0 to +60°C	≤ ± 50 ppb	≤ ± 25 ppb
B = -20 to +70°C	≤ ± 100 ppb	≤ ± 50 ppb
C = -40 to +85°C	≤ ± 150 ppb	≤ ± 100 ppb

TABLE 2: Idd

Temperature	Vdd = 3.3V	Vdd = 5V
25°C -20°C	≤ 120 mA ≤ 170 mA	≤ 80 mA ≤ 120 mA
start-up current at 25°C duration	≤ 350mA 30s	≤ 300mA 10s

TABLE 3:

Frequency control adjustment response slope positive	Vdd = 3.3V	Vdd = 5V
Voltage control input impedance > 47kΩ	0 to 3.3V	0.5 to 5V
Resistor control R connect pin 1 to ground (Input impedance > -4,7kΩ)	0 to 10kΩ	0 to 10kΩ
No frequency control YA or YB	Pin 1 connect to GND	



Micro Crystal AG
Mühlestrasse 14
CH-2540 Grenchen
Switzerland

Tel. +41 32 655 82 82
Fax +41 32 655 80 90
sales@microcrystal.com
www.microcrystal.com

STANDARD FREQUENCIES:

Frequency «MHz»			
10	20	40	50
54	100	108	120
Other frequencies from 10 MHz up to 120 MHz on request			

ENVIRONMENTAL CHARACTERISTICS:

Storage temp. range	-55 to +125°C
Vibration resistance	10 to 2000Hz / 20g
Shocks resistance	5000g / 0.3ms / ½ sine

TERMINATIONS AND PROCESSING:

Pin soldering	+235°C / 10s max +260°C / 5s max
Package SMD version option D1 or D2 see application note	Dil 14.4 pins GND to case height = 8mm

PRODUCT DESCRIPTION AND ORDERING INFORMATION:

SCOCXOH V T - C V5 20MHz XXX

W = Vdd 3.3V
V = Vdd 5V

T = high stability
blank = standard stability

A = 0 to +60°C
B = -20 to +70°C
C = -40 to +85°C
X = custom

R1 = R = 0 to 10kΩ
V3 = Vc = 0 to 3.3V
V5 = Vc = 0.5 to 5V

YA internal accuracy= ± 1ppm
YB internal accuracy= ± 0.5ppm
Y = custom

Frequency

customer spec N°

A unique part number will be generated for each product specification, i.e:
20xxxx-EA00 (in ESD plastic tray)
Please contact us.

All specifications subject to change without notice.



Micro Crystal AG
Mühlestrasse 14
CH-2540 Grenchen
Switzerland

Tel. +41 32 655 82 82
Fax +41 32 655 80 90
sales@microcrystal.com
www.microcrystal.com